



TPV INTÉGRÉS

www.ares.com



MOBILITÉ



KIOSKS



PANELS PC



IMPRIMANTES



AFFICHAGE



PÉRIPHÉRIQUES

AURES
TOUCH THE DIFFERENCE

MINI KOMET

Compact Self-Checkout KIOSK

17" interactive Countertop KIOSK Solution



The AURES **MINI KOMET** is the compact option (17" touchscreen) of the KOMET kiosk.

Based on the design of the KOMET range - but in a countertop version - the MINI KOMET offers small dimensions (377 x 188,5 x 542,3 mm); powerful and ergonomic, this kiosk solution has been developed for sales counters' environments where space is sometimes limited.

It integrates a 17" 4/3 YUNO Kiosk panel PC, an AURES ODP 444 receipt printer, a payment terminal (choice of several models), as well as a high-performance 2D barcode reader (Honeywell or Datalogic). An integrated light indicator (RGB LED) has been placed on the top of the kiosk to warn about any unavailability of the hardware or need for assistance.

The MINI KOMET self-checkout solution allows consumers to scan and pay for their purchases independently; this small kiosk is an essential complement to traditional checkout POS or mobile POS systems in many sectors (snacking, grocery stores and mini-markets, take-away sales, etc.).



TOUCH THE DIFFERENCE



KIOSKS

MINI KOMET

Special «countertop» kiosk in compact format

4/3 touchscreen (YUNO Kiosk 17")

10 point multi-touch projective capacitive panel (PCAP)

3 processors to choose from: i5, i3 or J1900

SSD 2.5" 128 GB

4 GB of memory as standard, expandable to 8 GB

Autonomous centralized payment terminal

ODP 444 thermal receipt printer 80 mm (integrated)

Integrated light indicator



SYSTEM YUNO KIOSK 17"

Processor	i5-5350U, i3 -5010U Broadwell or Intel Bay Trail J1900
Memory	DDR3 SODIMM 4 GB in standard (up to 8 GB)
SSD	2,5" 128 GB (2 slots)
LCD	17" TFT (1280 x 1024)
Touch screen	Flat & Edgeless PCAP Panel
Scanner	Honeywell CF3680 Standard / Datalogic Magellan 1500

OTHER SYSTEMS

Scanners	Honeywell CF3680 Standard / Datalogic Magellan 1500
Printer	thermal receipt printer ODP 444

INPUTS/OUTPUTS

Serial ports	4 ports (+ power supply 5/12 V for COM3 / COM4)
USB	5 x USB 2.0 + 1 x USB 3.0 (J1900 version) 4 x USB 2.0 + 2 USB 3.0 (i5 & i3 versions)
LAN	10/100/1000 Base-T
Audio	Internal loudspeaker, headphones / microphone jack

PAYMENT TERMINAL - SEVERAL CHOICES OF PED BRACKET AVAILABLE FOR INTEGRATION

Verifone	VX820 / P400
Ingenico	LANE 5000 / IPP 350

MISCELLANEOUS

CEM	CE Directive CEM 2014/30/EU (Class B)
Safety	CE Directive BT 2014/35/EU
Operating temperature	5 - 35° C
Front Panel	Splash & Dust Resistant (IP54)
Colours	Black or white
Dimensions (L x D x H mm)	377 x 188,5 x 542,3
Weight	32 kg
LED indicator	integrated
Compatibles OS	Windows 10 IoT Enterprise, Linux

Photos et informations non contractuelles, sujettes à modifications sans préavis - © AURES - 2020-2